interstuhl

Technical data sheet 650P

Specification Conference chair with seat height adjustment

Dimensions in	Backrest:	H:	455
	Seat:	H:	420-565
		W:	400
		D:	415
	Total:	H:	1015
		W (no AR):	570
		L:	700
Packaging data	Weight:	kg	7
	Volume:	m³	0,2



Basic equipment		Benefit
Seat shell	Colour maintained throughout plastic parts, black.	Thus "colourfast" with deep scratches and abrasions.
Seat height adjustment	Seat height adjustment infinitely variable from 420- 565 mm. Self- supporting safety gas spring. Patented base seat height adjustment.	Even those outside the DIN range (i.e. taller than 192 cm and smaller than 151 cm) are offered the correct ergonomic posture.
Base	Colour maintained throughout plastic base, black.	Thus "colourfast" with deep scratches and abrasions.
Castors Ø 65 mm	Hard double castors, load- dependent braked, for soft floors. (acc. to DIN EN 12529)	The chair does not roll away in an off- loaded position, minimum risk of accident.
Materials	All materials are segregated and recyclable.	Environmentally friendly.
Standards	EN 1335 for office swivel chairs and office swivel armchairs. GS-symbol for tested safety, ergonomics and toxic agents.	High safety and comfort.
Certification	Quality management system DIN EN ISO 9001:2000, EMAS acc. to EC Directive 761/2001, Environmental management system DIN EN ISO 14001:2005.	High quality product.
Warranty and return	5 years long term and 3 years full warranty. Complete return and recycling guarantee.	Exchange of parts free of charge, within the guaranteed period.

interstuhl

Technical data sheet 650P

Specification Conference chair with seat height adjustment

Dimensions in	Backrest:	H:	455
	Seat:	H:	420-565
		W:	400
		D:	415
	Total:	H:	1015
		W (no AR):	570
		L:	700
Packaging data	Weight: Volume:	kg m³	7 0,2



Options		Benefit
Plastic parts	Seat shell and base in plastic cream white or ice- blue. (Adjusting lever and operational controls always black).	The chair range is available in several colours. Visual appeal.
Upholstery for the seat and back	10 mm foam. Upholstery is unglued, ensuring optimal air movement, breathable. Fabric and leather collections are available in various colours.	Afterwards easy to assemble and to retrofit. Good seating comfort. Visual appeal.
Castors Ø 65 mm	Soft double castors, load- dependent braked, for hard floors or glides. (acc. to DIN EN 12529)	The chair does not roll away in an off- loaded position, minimum risk of accident.
Base	Alumimium powder- coated, brilliant silver, black or alumimium polished.	Stability, longevity.
Sprung column	Also possible in the lowest position.	Cushions the impact of sitting down, and gentle on the spine.